


# AD 550

Doosan  
Mecc Alte  
D+ &



ISO8528

GC, ) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#( #

z) \$ z' z' D:

	"	kw	"	kw	Amp
400/230	550,00	440,00	500,00	400,00	722,00

fPQDE

GC, ) &

,) & z

fDF DE

%\$1

% %&

GC" \$(\*\*

z&(

GC

## Standard Specifications

z

fl

E

z

z

## ALTERNATOR

D; A Z'5JF

## TRANSFER SWITCH

# AD 550

Doosan  
Mecc Alte  
D+' &''

Manufacturer	Doosan		
Model	P180LE		
		494,00 kw [662,50HP]	
	L	18,300	
	"	128 x 142	
		15,0:1	
	fl # 7	"# "	1500
	fl 7	L	35,00
		L	91,00
AbsorbedAirDischargeReSourceKey.Text	' # "	33,70	
	' # "	565,00	
	' # "	97,90	
	° C	580,00	
		24 V d.c.	
	Load	%\$i	+) i
	# "	) \$i	
		111,60	81,30 54,80

	Mecc Alte		
	ECO 40-3S/4		
	Hz	50	
	"	500,00	
7cg'		0,80	
		3	
	fl 7	400/230	
	A	722,00	
Temperature		H	

		fl 7		fl 7	
	"	"	"	"	L
AD 550	3600,00	3264,00	1550,00	1991,00	850,00
		fl 7		fl 7	
	"	"	"	"	L
MS 80	4790	4810	1606	2615	850





# AD 550

Doosan  
Mecc Alte  
D+' &'



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1606
fl "L	"	4810
fl "L	"	2615
	L	850